



DECORDRUM



PDR200

DECORDRUM

- Two models, Decordrum 200 and Decordrum 250 with black base and snap on opal diffuser
- Decordrum 250 has clear prismatic option for extra light output.
- Compact fluorescent version PDR62 (Decordrum 200) supplied complete with 3500K-16W TC-DD lamp
- GLS lamps not inc.
-  Suitable for mounting on normally flammable surfaces
- Wall or ceiling mounting



DECORDRUM 200

- Electrical protection- GLS models Class II, compact fluorescent Class I
- IP rating: compact fluorescent IP44, GLS models IP20 (external wiring termination - not suitable where water is present)

60 watt B22d	PDR200	(Bulk Pack Version PDR201)
16 watt TC-DD	PDR62	(supplied with lamp)

EMERGENCY LIGHTING VERSION

- The compact fluorescent, PDR62 is available with a 3 hour self-contained emergency lighting kit mounted in a remote steel enclosure joined by a 0.5m flexible conduit wiring harness.
- To specify add suffix **/EM3** eg. **PDR62/EM3**


POWER FACTOR CORRECTION

Available as an optional extra for all fluorescent versions. To specify add suffix **/PF**

DECORDRUM 250



PDR250



- Electrical protection class II.
- IP20 - external wiring terminations - not suitable where water is present
- 100 watt versions are injection moulded in polycarbonate


60 watt (max) B22d	PDR160	opal diffuser (Bulk pack version PDR161)
100 watt (max) B22d	PDR250	opal diffuser (Bulk pack version PDR251)
100watt (max) B22d	PDX250	clear prismatic

Smart, versatile luminaires for general lighting purposes. Ideal for use in bars, toilets, porches, lobbies, staircases etc.

DECORBRIK



PDB100




- Electrical protection class II
- IP20 - external wiring terminations - not suitable where water is present
- 75 watt B22d lamp max (lamp not inc.) or compact fluorescent electronic energy saving lamp 20 watt max B22d cap. Max overall length 165mm
- Black polycarbonate body with white opal polycarbonate diffuser
- Smart clean lines. Wall or ceiling mounting in porches, corridors, stairs, landings etc
- ▽ Suitable for mounting on normally flammable surfaces

PDB100

DECORSQUARE



PDS100



- Electrical protection class II
- IP20 - external wiring terminations - not suitable where water is present
- 100 watt B22d lamp max (lamp not inc.) or compact fluorescent electronic energy saving lamp 20 watt max B22d cap. Max overall length 165mm
- Black polycarbonate body with white opal polycarbonate diffuser
- Smart clean lines. Wall or ceiling mounting in porches, corridors, stairs, landings etc
- ▽ Suitable for mounting on normally flammable surfaces

PDS100



FOR SALES AND INFORMATION:

TEL: +45 36 72 22 00 EMAIL: mail@elthermo.dk

FAX: +45 36 41 07 41 WEB: www.elthermo.dk