


Surface Luminaire DECORTRIM 400



PDR516

DECORTRIM 400

- Decorative, stylish and functional with a choice of 3 trim finishes, opal or prismatic diffuser and 16, 28 or 38watt TC-DD lamps
- Injection moulded in polycarbonate with snap-in diffuser
- Supplied complete with 3500K lamp
- IP44 Suitable for indoor or sheltered areas
- ∇ Suitable for mounting on normally flammable surfaces
- Electrical protection class I



WHITE TRIM



PDX517

	Opal	Prismatic	Emergency
16W TC-DD	PDR517	PDX517	/SC3
28W TC-DD	PDR529	PDX529	/SC3
38W TC-DD	PDR539	PDX539	/SC3

BRASS TRIM



PDX516

	Opal	Prismatic	Emergency
16W TC-DD	PDR516	PDX516	/SC3
28W TC-DD	PDR528	PDX528	/SC3
38W TC-DD	PDR538	PDX538	/SC3

CHROME TRIM



PDR518

	Opal	Prismatic	Emergency
16W TC-DD	PDR518	PDX518	/SC3
28W TC-DD	PDR530	PDX530	/SC3
38W TC-DD	PDR540	PDX540	/SC3

BRASS TRIM WITH FINIAL



PDX515

	Opal	Prismatic	Emergency
16W TC-DD	PDR515	PDX515	/SC3
28W TC-DD	PDR527	PDX527	/SC3
38W TC-DD	PDR537	PDX537	/SC3

EMERGENCY VERSIONS

Maintained, self-contained, 3-hour emergency versions available. The emergency module and batteries are fully integral and are specified by adding the suffix **/SC3** to the required model e.g. **PDR538/SC3**

HIGH FREQUENCY OPTION - BENEFITS

- As much as 25% less energy usage over conventional ballasts
- Up to 50% longer lamp life
- Constant and optimum lamp running characteristics
- Flicker free operation
- Complies with safety and EMC performance standards. To specify add suffix **/HF** to above codes e.g. **PDX529/HF**

POWER FACTOR CORRECTION

Available as an optional extra for all fluorescent versions. To specify add suffix **/PF**

FOR SALES AND INFORMATION:

TEL: +45 36 72 22 00 EMAIL: mail@elthermo.dk

FAX: +45 36 41 07 41 WEB: www.elthermo.dk


DECORTRIM 310



PDR718

DECORTRIM 310

- Injection moulded polycarbonate with choice of snap on opal or prismatic diffuser
- Supplied complete with 16-watt TC-DD 3500K lamp
- IP44 suitable for indoor or sheltered areas
- ∇ Suitable for mounting on normally flammable surfaces
- Electrical protection class I



DECORTRIM 310, 16W TC-DD

	Opal	Prismatic	Emergency
Chrome trim	PDR718	PDX718	/EM3
White trim	PDR717	PDX717	/EM3
Brass trim	PDR716	PDX716	/EM3
Brass trim with finial	PDR715	PDX715	/EM3

EMERGENCY VERSION

Maintained 3 hour emergency versions are supplied with the emergency module and batteries in a separate steel enclosure connected to the luminaire via a 0.5m flexible conduit wiring harness. To specify add suffix **/EM3** e.g. **PDR717/EM3**

HIGH FREQUENCY OPTION

- As much as 25% less energy usage over conventional ballast up to 50% longer lamp life
- Constant and optimum lamp running characteristics
- Flicker free operation
- Complies with safety and EMC performance standards

To specify add suffix **/HF** to above codes e.g. **PDX718/HF**

POWER FACTOR CORRECTION

Available as an optional extra for all fluorescent versions. To specify add suffix **/PF**

Neat stylish and compact range of luminaires for general use in more discerning installations. Localised wall or ceiling lighting in banks, building societies, hotels, bars, porches etc. Each version supplied complete with 16-watt TC-DD low energy lamp.