

Halogen Floodlight

NORSElight



FH 200 D
FH 300 D
FH 500 D

Features

- Designed to meet applicable marine requirements IP66
- Horizontal and vertical mounting
- Front ring with snap coupling simplifies lamp change
- Front ring, snap coupling and bracket of stainless steel
- Front ring gasket of heat resistant silicon rubber
- House in seawater resistant aluminium finished in white Corrocoat polyester
- Hardened front glass
- Reflector in oxidized and polished aluminium.

Applications

The Norselight halogen floodlight family is designed to achieve the highest levels of durability and performance under extreme environmental conditions across a wide temperature range.

With Norselights wide range of floodlight power ratings combined with our computerised light calculation system, we are able to offer our customers optimal arrangement of fittings, ensuring maximum safety of both personnel and equipment.



Technical data

NORSElight

FH 200 D, FH 300 D, FH 500 D

Data	Voltage (Volt)	Power (Watt)	Socket	Lamp lifetime* (h)	Luminous flux (Lumen)	Weight (Kg)
FH 200 D	12	2 x 100	GY 6,35	2000	2500	3
	24	2 x 100			2000	3
FH 300 D	230	300	R7S	2000	4800	3
FH 500 D	230	500	R7S	2000	9500	3

*Accordance to manufactures spesification

